

## Bamboo / Wood oil

Impregnator for outdoor wooden decking floors

### TECHNICAL DATASHEET

#### ▣ Description

WOOD OIL is an outdoor wood impregnator particularly recommended for the treatment of outdoor wooden floors (swimming pool edges, verandas, walkways), window and door frames, fences and canopies made of wood. It contains natural and synthetic oils, with the addition of UV ray absorbers and special anti-ageing ingredients against the wood decay. It doesn't crack. Doesn't degrade rubbers and expansion joints. It is recommended anyway to make some tests before application.

#### ▣ Characteristics

Mixture ratio	single-component
Application temperature	+10°C ÷ +25°C
Coverage	1L/13 m2 circa
Application	brush, immersion
Dust dry	6h (1)
Fingerprint dry	24h (1)
Storage stability	1 year (2)
Packaging	1 L - 5 L
Sanding	do not sand

1 at 20° and 65% R.H.

2 in original sealed containers at temperatures between +10°C and +25°C

#### ▣ How to use

Shake well before use. Before applying WOOD OIL, prepare the wood, preferably with 120/150 sandpaper. Apply the first coat of WOOD OIL. Apply a second coat of the product after 24/48 hours, without sanding.

#### ▣ Warnings

Cloths, sponges, brush used for the application (even sanding dust), must be soaked immediately after use in order to avoid the risk of self-ignition.

#### ▣ Label elements

- Flammable liquid and vapour. · May be fatal if swallowed and enters airways. · Harmful to aquatic life with long lasting effects.
- Repeated exposure may cause skin dryness or cracking. · Contains . May produce an allergic reaction.
- Keep out of reach of children. · Keep away from heat / sparks / open flames /hot surfaces. No smoking. · Wear protective gloves / protective clothing / eye protection / face protection. · DO NOT induce vomiting. · Dispose your waste in dedicated collection points.

Contents: 1-(METHYL)-8-(1,2,2,6,6-PENTAMETHYL -4-PIPERIDINYL) SEBACATE; HYDROXYPHENYL BENZOTRIAZOL DERIVATIVES; 3-ODIO-2-PROPYNYL BUTYLCARBAMATE; 2-BUTANONE OXIME; BIS(1,2,2,6,6-PENTAMETHYL-4- PIPERIDYL) SEBACATE ; Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics; NAPHTHA (PETROL.) HYDROTREATED HEAVY; XYLENE (MIXTURE OF ISOMERS); ETHYLBENZENE ;

